

AXIS 206 Network Camera

The smallest network camera
in the world

The AXIS 206 Network Camera offers a cost-effective solution for remote indoor monitoring and surveillance over a local area network or the Internet. This network camera is ideal for use in small and mid-sized businesses and homes.

Small enough to fit in the palm of your hand, the AXIS 206 delivers high quality Motion JPEG video using a progressive scan CMOS image sensor and advanced signal processing techniques. The AXIS 206 has a multilingual user interface and together with the free AXIS Internet Dynamic DNS Service it is easy to install, set up and access the AXIS 206 from anywhere over the Internet. It also includes free video management software for easy viewing, management and recording. Use your browser to view live video streams, or use the platform-independent AXIS VAPIX API to integrate the camera into a surveillance system.

The Ethernet-based AXIS 206 Network Camera can operate in light conditions as low as 4 lux, and provides high quality images at up to 30 frames per second in all resolutions, up to VGA 640x480 pixels.



NVR-PRO
NETWORK VIDEO RECORDING
MANAGEMENT & TRANSMISSION

www.NVR-PRO.com



- High quality Motion JPEG Video Stream
- Up to 30 frames per second in VGA resolution
- Built-in Web server for easy monitoring
- Multilingual user interface
- Easy installation, configuration and management

AXIS[®]
COMMUNICATIONS
Make your network smarter

AXIS 206 Network Camera

Specifications			
Image sensor	1/4" Progressive Scan CMOS	Minimum Web browsing requirements	Pentium III CPU 500 MHz or higher, or equivalent AMD 128 MB RAM AGP graphic card, Direct Draw, 32 MB RAM Windows XP, 2000, Server 2003, DirectX 9.0 or later Internet Explorer 6.x or later For other operating systems and browsers see www.axis.com/techsup
Lens	F2.0, 4.0 mm, fixed iris, horizontal viewing angle: 54°		
Illumination	4 - 10 000 lux		
Video compression	Motion JPEG		
Resolutions	640x480, 320x240, 160x120		
Frame rate	Up to 30 frames per second in all resolutions		
Image settings	Compression levels: 100 Rotation: 0°, 180° Configurable color level, brightness, contrast, white balance Overlay capabilities: time, date and text		
Shutter time	1/2 - 1/10 000 second		
Language support	Chinese, English, French, German, Italian, Japanese, Korean and Spanish		
Security	Multiple user access levels with password protection		
Users	10 simultaneous viewers	Supported protocols	IP, HTTP, TCP, ICMP, UDP, SMTP, FTP, DHCP, UPnP, Bonjour, ARP, DNS, DynDNS, NTP More information on usage available at www.axis.com Bonjour is a trademark of Apple Computer, Inc., registered in the U.S. and other countries
Processors and memory	CPU: 32-bit RISC Motion JPEG compression chip RAM: 16 MB Flash: 4 MB	Video management software (not incl.)	AXIS Camera Station – Surveillance application for viewing, recording and archiving See www.axis.com/partner/adp_partners.htm for more software applications via partners
Power	5.0 - 5.5 V DC Min 400 mA	Included accessories	Power supply, stand, Installation Guide, CD with installation tool, software and User's Manual, video management software
Operating conditions	5 - 40 °C (41 - 104 °F) Humidity 20 - 80% RH (non-condensing)	Accessories (not incl.)	AXIS 206/207 Vandal Resistant Housing
Installation, management and maintenance	Installation tool on CD and Web-based configuration Configuration backup and restore One-click installation with Internet Dynamic DNS (free service from Axis) Firmware upgrades over HTTP or FTP, firmware available at www.axis.com	Approvals	EN 55022 Class B, EN 61000-3-2, EN 61000-3-3, EN 55024, EN 61000-6-1 FCC part 15 Subpart B Class B VCCI Class B, ICES-003, C-Tick AS/NZS 3548, EN 60950 Power supply: UL, CSA, EN 60950
Video access from Web browser	Camera live view, customizable HTML pages	Dimensions (HxWxD) and weight	85 x 55 x 34 mm (3,35" x 2,17" x 1,34") 177 g (6,24 oz) incl. stand, excl. power supply



www.NVR-PRO.com

Toll Free: 1.888.919.2263
International: +1.845.343.4077
Fax: +1.845.343.4299

